




Model Number

NMB1,5-8GM35-E0-FE-150MM-V1


Features

- Stainless steel sensing face
- Sensing range 1.5 mm
- 3-wire DC

Connection



Pinout




Wire colors in accordance with EN 60947-5-2

1	BN
3	BU
4	BK

Accessories

- V1-G-2M-PUR**
Cable socket, M12, 4-pin, PUR cable
- V1-W-2M-PUR**
Cable socket, M12, 4-pin, PUR cable

Dimensions



Technical Data

General specifications

Switching element function		NPN	NO
Rated operating distance	s_n	1.5 mm	
Installation		embeddable	
Output polarity		DC	
Assured operating distance	s_a	0 ... 1.215 mm	
Actuating element		Ferrous targets	
Reduction factor r_{Al}		0	
Reduction factor r_{Cu}		0	
Reduction factor r_{V2A}		0.6	
Reduction factor r_{St37}		1	
Reduction factor r_{Brass}		0	

Nominal ratings

Operating voltage	U_B	10 ... 30 V DC	
Switching frequency	f	80 Hz	
Hysteresis	H	3 ... 15 typ. 5 %	
Reverse polarity protected		yes	
Short-circuit protection		yes	
Voltage drop	U_d	≤ 2 V	
Operating current	I_L	≤ 100 mA	
Current consumption		≤ 15 mA	
Off-state current	I_r	≤ 10 μ A	

Indicators/operating means

Operating display	LED red: output
-------------------	-----------------

Standard conformity

Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007
-----------	---

Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

Mechanical specifications

Connection type	Cable connector M12 x 1, 3-pin with PUR cable 150 mm
Core cross-section	0.14 mm ²
Housing material	Stainless steel 1.4305 / AISI 303
Sensing face	Stainless steel 1.4305 / AISI 303
Protection degree	IP67

Approvals and certificates

UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Products with a maximum operating voltage of ≤ 36 V do not bear a CCC marking because they do not require approval.

Release date: 2010-11-16 13:56 Date of issue: 2010-11-17 904813_ENG.xml